

Printing Date 06/02/2016 Revision Number 2 Revision Date 06/02/2016

1 Identification

· Product identifier

· Trade name: 05213 TRUE GRIP (SILAPRENE) ADHESIVE

· Article number: 05213

· Relevant identified uses of the substance or mixture. Adhesive

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

Royal Adhesives And Sealants, LLC

2001 W. Washington Street

South Bend IN 46628-2023

Information Phone Number: 574-246-5000

· Information department: Environment protection department.

· Emergency telephone number:

ChemTrec: Day or Night within USA and Canada: 1-800-424-9300. Outside USA and Canada: +1 703-527-3887 (collect calls accepted)

2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS07

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS02

GHS07

- · Signal word Danger
- · Hazard statements

Highly flammable liquid and vapor.

Causes serious eye irritation.

May cause drowsiness or dizziness.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment.

Avoid breathing dust/fume/gas/mist/vapors/spray

(Contd. on page 2)

Printing Date 06/02/2016 Revision Number 2 Revision Date 06/02/2016

Trade name: 05213 TRUE GRIP (SILAPRENE) ADHESIVE

(Contd. of page 1)

Wear protective gloves / eye protection / face protection.

Ground/bond container and receiving equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a POISON CENTER/doctor if you feel unwell.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use for extinction: CO2, powder or water spray.

Store locked up.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 1Fire = 3Reactivity = 0

· HMIS-ratings (scale 0 - 4)



- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Adhesive

· Hazardous components:				
67-64-1	acetone	50-100%		
141-78-6	ethyl acetate	5-20%		
109-99-9	tetrahydrofuran	2.5-10%		

4 First-aid measures

- · Description of first aid measures
- · After inhalation:

Supply fresh air or oxygen; call for doctor.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact: Immediately wash with water and soap and rinse thoroughly.

(Contd. on page 3)

Printing Date 06/02/2016 Revision Number 2 Revision Date 06/02/2016

Trade name: 05213 TRUE GRIP (SILAPRENE) ADHESIVE

(Contd. of page 2)

· After eye contact:

Rinse opened eye for 20 minutes under running water. If eye becomes irritated, obtain medical treatment.

- · After swallowing: Do not induce vomiting; immediately call for medical help.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray.

Use fire fighting measures that suit the environment.

· Advice for firefighters

Firefighters use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

· Protective equipment: Protective clothing and respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of contaminated material as waste in accordance with federal state and local regulations.

 $Ensure\ adequate\ ventilation.$

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Avoid prolonged or repeated contact with skin.

Avoid contact with eyes.

Wash thoroughly after handling.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Open and handle receptacle with care.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep container closed when not in use.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location away from direct heat.

(Contd. on page 4)

Printing Date 06/02/2016 Revision Number 2 Revision Date 06/02/2016

Trade name: 05213 TRUE GRIP (SILAPRENE) ADHESIVE

(Contd. of page 3)

· Information about storage in one common storage facility:

Store away from oxidizing agents.

Store as flammable liquid.

- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters

· Components with limit values that require monitoring at the workplace:

67-64-1 acetone

PEL Long-term value: 2400 mg/m³, 1000 ppm REL Long-term value: 590 mg/m³, 250 ppm TLV Short-term value: 1187 mg/m³, 500 ppm Long-term value: 594 mg/m³, 250 ppm BEI

141-78-6 ethyl acetate

PEL Long-term value: 1400 mg/m³, 400 ppm REL Long-term value: 1400 mg/m³, 400 ppm TLV Long-term value: 1440 mg/m³, 400 ppm

109-99-9 tetrahydrofuran

PEL Long-term value: 590 mg/m³, 200 ppm

REL Short-term value: 735 mg/m³, 250 ppm

Long-term value: 590 mg/m³, 200 ppm

TLV Short-term value: 295 mg/m³, 100 ppm

Long-term value: 147 mg/m³, 50 ppm

Skin

· Ingredients with biological limit values:

67-64-1 acetone

BEI 50 mg/L

Medium: urine Time: end of shift

Parameter: Acetone (nonspecific)

109-99-9 tetrahydrofuran

BEI 2 mg/L

Medium: urine Time: end of shift

Parameter: Tetrahydrofuran

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment (see listings below)
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

(Contd. on page 5)

Printing Date 06/02/2016 Revision Number 2 Revision Date 06/02/2016

Trade name: 05213 TRUE GRIP (SILAPRENE) ADHESIVE

(Contd. of page 4)

· Breathing equipment:

Use approved respiratory protection equipment when airborne exposure is excessive. Consult the respirator manufacturer to determine the appropriate type of equipment for a given application. Observe respirator use limitations specified by the manufacturer.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· Eye protection:



Tightly sealed goggles

Safety glasses with side shields.

Use full face shield over protective eye wear when there is a risk of a splash.

· Body protection: Protective work clothing

9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Liquid Color: Clear

· Odor: Characteristic

· Change in condition

Melting point:Undetermined.Boiling point:55 °C (131 °F)

• Flash point: $-21 \, ^{\circ}C \, (-6 \, ^{\circ}F)$

• Ignition temperature: $230.0 \, ^{\circ}C \, (446 \, ^{\circ}F)$

· Auto igniting: Product is not selfigniting.

· Danger of explosion: NONE

· Flammable limits:

 Lower:
 1.5 Vol %

 Upper:
 13.0 Vol %

· Vapor pressure at 20 °C (68 °F): 233.0 hPa (175 mm Hg)

• Specific gravity: 0.885

· Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

(Contd. on page 6)

Printing Date 06/02/2016 Revision Number 2 Revision Date 06/02/2016

Trade name: 05213 TRUE GRIP (SILAPRENE) ADHESIVE

(Contd. of page 5)

· Viscosity:

Dynamic: Not determined. **Kinematic:** Not determined.

· Solvent content:

Organic solvents: 77.6 %

Other information VOC: = 2.13 LBS/GAL

WEIGHT PER GALLON: = 7.36 LBS

10 Stability and reactivity

· Reactivity No further relevant information available.

- · Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

- · **Possibility of hazardous reactions** No further information is available.
- · Conditions to avoid Heat, flames, sparks, hot surfaces, ignition sources.
- · Incompatible materials: Strong oxidizers, acids, and bases.
- · Hazardous decomposition products: Oxides of carbon and nitrogen.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50 values	that are re	levant for c	lassification:
------------------	-------------	--------------	----------------

67-64-1 acetone

 Oral
 LD50
 5800 mg/kg (rat)

 Dermal
 LD50
 20000 mg/kg (rabbit)

109-99-9 tetrahydrofuran

Oral LD50 2500 mg/kg (rat)

- · Primary irritant effect:
- · on the skin: May irritate the skin.
- on the eye:

Causes serious eye irritation.

Vapors may be irritating to the eyes.

- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

(Contd. on page 7)

Printing Date 06/02/2016 Revision Number 2 Revision Date 06/02/2016

Trade name: 05213 TRUE GRIP (SILAPRENE) ADHESIVE

(Contd. of page 6)

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes: At present there are no ecotoxicological assessments.
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation: Must be specially treated adhering to official regulations.
- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

UN1133

14 Transport information

- · UN-Number
- · DOT, ADR, IMDG, IATA

· UN proper shipping name

· DOT, IMDG, IATA ADHESIVES

· ADR 1133 ADHESIVES

- · Transport hazard class(es)
- $\cdot DOT$



· Class 3 Flammable liquids

· Label

· ADR, IMDG, IATA



· Class 3 Flammable liquids

(Contd. on page 8)

Printing Date 06/02/2016 Revision Number 2 Revision Date 06/02/2016

Trade name: 05213 TRUE GRIP (SILAPRENE) ADHESIVE

		(Contd. of page 7)
· Label	3	
· Packing group · DOT, ADR, IMDG, IATA	III	
· Environmental hazards: · Marine pollutant:		
· Special precautions for user	Warning: Flammable liquids	
· Transport in bulk according to Annex I MARPOL73/78 and the IBC Code	I of Not applicable.	
· UN "Model Regulation":	UN1133, ADHESIVES, 3, III	

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

· TSCA (Toxic Substances Control Act):

All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements.

- · Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· (DSL) Canada Dosmestic Substance List

All components of this product are on the DSL(Canada Domestic Substance list) or are exempt from DSL requirements.

Non Iona					
	ey Right-to-Know List:				
67-64-1	acetone				
141-78-6	ethyl acetate				
109-99-9	tetrahydrofuran				
· New Jers	ey Special Hazardous Substance List:				
67-64-1	acetone	F3			
141-78-6	ethyl acetate	F3			
109-99-9	tetrahydrofuran	F3, R1			
· Pennsylva	Pennsylvania Right-to-Know List:				
67-64-1	acetone				
141-78-6	ethyl acetate				
109-99-9	tetrahydrofuran				

(Contd. on page 9)

Printing Date 06/02/2016 Revision Number 2 Revision Date 06/02/2016

Trade name: 05213 TRUE GRIP (SILAPRENE) ADHESIVE

(Contd. of page 8) · Pennsylvania Special Hazardous Substance List: 67-64-1 acetone Е 141-78-6 ethyl acetate Е Ε 109-99-9 tetrahydrofuran · Cancerogenity categories · EPA (Environmental Protection Agency) 67-64-1 acetone 109-99-9 tetrahydrofuran SC· TLV (Threshold Limit Value established by ACGIH) 67-64-1 acetone A4109-99-9 tetrahydrofuran *A3* · MAK (German Maximum Workplace Concentration) 109-99-9 tetrahydrofuran 4 · NIOSH-Ca (National Institute for Occupational Safety and Health) None of the ingredients is listed.

· National regulations:

- · Water hazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

Although the information and recommendations set forth in this SDS are presented in good faith and are believed to be correct as of the date of this SDS, Royal Adhesives & Sealants makes no representations as to the completeness or accuracy thereof. Information is supplied on the condition that the persons receiving and using it will make their own determination as to the suitability for their purpose prior to use. In no event will Royal Adhesives & Sealants or any affiliate thereof be responsible for damages of any nature whatsoever resulting from the use or reliance on the information set forth in the SDS.

- · Department issuing SDS: Environment protection department.
- · Creation Date: 06/28/2013
- · Date of preparation / last revision 06/02/2016 / 1
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

(Contd. on page 10)

Printing Date 06/02/2016 Revision Number 2 Revision Date 06/02/2016

Trade name: 05213 TRUE GRIP (SILAPRENE) ADHESIVE

(Contd. of page 9)

PEL: Permissible Exposure Limit REL: Recommended Exposure Limit

BEI: Recommended Exposure Limit
BEI: Biological Exposure Limit
Flam. Liq. 2: Flammable liquids – Category 2
Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3