ANTI-STATIC COPPER TINSEL The Lowest Cost Static Eliminator Available

• QUALITY 100% COPPER

• NO POWER NEEDED

• HIGHLY EFFECTIVE



Proven through decades of success to be the most effective low cost, low maintenance passive static electricity eliminator available! TAKK tinsel is of high quality 100% copper

construction. The core is made of copper wire to ensure positive grounding and strength. The fine, sharply pointed copper strands provide greater static elimination. The highly conductive strands are interspersed to maximize effectiveness, but are not so dense as to make it easy to collect dust and particles. Tinsel resists breakage, matting and shedding. It is a self-energizing, induction type (no power needed) static eliminator which does not spark or cause sparks, and can be used in hazardous conditions. Effectiveness increases as static increases. Typical applications for TAKK Anti-Static Tinsel include Printing, Textile, Converting, Plastics, and anywhere there are moving webs and conveyors. Special applications include Office Machines, Fitness Equipment and Ticket Dispensers.

Part #5020 Tinsel Coils:

Available in two 1.25 inch diameter x 36 foot coils (total 72 foot) or in custom pre-cut lengths. Standard or specially designed fastening and grounding accessories are sold separately for custom static solutions.

Part #5027 Reel of 504 Ft.Tinsel:

The same copper quality and 1.25 inch diameter as Model 5020. This larger reel length costs less per foot. Allows tinsel to be conveniently stored on a spindle close to production machinery and provides a continuous length for applications that require long lengths.



OEM Availability:

Specially available to original equipment manufacturers to meet standard, custom or unique requirements. Consult factory.

Visit www.statictinsel.com for other passive eliminators



TAKK INDUSTRIES INCORPORATED

8665 E. Miami River Rd. Cincinnati, OH 45247 USA Fax (513) 353-4315 Phone (800) 792-8255 or (513) 353-4306 www.statictinsel.com www.takk.com sales@takk.com