

# Evo 4DLF



## Evo4 Dryer Light Finisher

Vianord offers this solution to combine in a unique unit the dryer and light finisher sections. This unit is available for plates size up to 120 x 160 cm (47 x 63 inch).

### DRYER SECTION

- 60 Celsius degree hot air (140 degree Fahrenheit)
- 6 drawers with individual timers
- 3 heating sections with separate temperature control and air circulation (2 drawers each)
- Uniform temperature for excellent drying result
- Safety thermostat in every section
- Exhaust system integrated
- Safety device for exhaust control
- Touch screen operator display
- Programmable unit warm up
- Automatic switch off after last plate

### LIGHT FINISHER SECTION:

- UVA + UVC lamps for post exposure and light finishing
- Programmable operation: simultaneous/separate/sequential
- Separate timers for UVA and UVC
- Automatic plate cooling with programmable time
- 24 programmable channels for different plate types
- Powerfull air exhaust with delayed stop for safe zone extraction
- Fiber optic lamp failure detectors
- Exhaust system integrated
- Touch screen operator display





### Dimensions LxWxH



1670 x 2030 x 1260 mm  
65.7 x 96.5 x 49.6 inches

### Power supply



400V 3PH/N/PE 50/60Hz 9.5kW 15A  
230V 3PH/PE 50/60Hz 9.5kW 26A

### Plate thickness



Up to 7 mm / 0.276 inch

### Solvent



n/a

### Packaging dimensions



2780 x 1950 x 2230 mm | 1.320 Kg

### Weight

1040 kg | 2292 pounds



### Maximum plate size

120 x 160 cm | 47 x 63 inches



### Compressed air supply

n/a



### Exhaust

2 x 140 mm Ø - 1200 m<sup>3</sup>/h  
1 x 60 mm Ø - 80 m<sup>3</sup>/h



### Remote monitoring

Optional



**Vianord**  
engineering  
[www.vianord.com](http://www.vianord.com)  
[info@vianord.com](mailto:info@vianord.com)

© 2015 Vianord. All rights reserved. The Vianord Logo®, Easy to Plate™ and Evo™ are registered trademarks or trademarks of Vianord Engineering SAS or its affiliates. All technical information set out herein is provided free of charge and is based on technical data, which Vianord believes to be reliable. It is intended for use by persons having skill, at their own discretion and risk. The handling precaution information contained herein is given with the understanding that those using it will satisfy themselves that their particular conditions of use present no health or safety hazards. Since conditions of product use are outside of our control we make no warranties express or implied in relation thereto and therefore cannot accept any liability in connection with any use of this information. Vianord Engineering SAS reserves the right to change the specifications of its products at any time. Nothing herein is to be taken as a license to operate under, or a recommendation to infringe any patents.